


CATALYTIC OXIDATION APPARATUS

Patent number: JP55056823
Publication date: 1980-04-26
Inventor: IZUMO MASAKADO; KOMURA MASAHARU;
KAMETANI KEIICHIROU
Applicant: DAIKIN IND LTD
Classification:
- International: *B01J8/04; B01J12/00; B01J19/24; B01J35/04;
F01N3/20; F01N3/28; F28D9/00; B01J8/04; B01J12/00;
B01J19/24; B01J35/00; F01N3/20; F01N3/28;
F28D9/00; (IPC1-7): B01D53/36*
- european: B01J8/04; B01J12/00P; B01J19/24R2; B01J35/04;
F01N3/20B2; F01N3/28B4B; F01N3/28D; F01N3/28D6;
F28D9/00K
Application number: JP19780129217 19781019
Priority number(s): JP19780129217 19781019

Also published as: DE2942359 (A1)**Report a data error here****Abstract of JP55056823**

PURPOSE:To improve greatly heat recovery rate of a catalytic oxidation apparatus by placing in shell a heat exchange structure and catalyst forming gas passages passing across each other at right angles every step consisting of corrugated sheets, etc. and arranging them in such a manner that introducing gas exchanges heat for exhaust gas. **CONSTITUTION:**Honeycomb catalyst structure C (an oxidation catalyst is deposited on part of passage) has gas passage passing across each other at right angles every step consisting flat sheets 1, 1 such as asbestos paper and corrugated sheets 2, 2. The honeycomb catalyst structure C and heat exchange structure E are placed in parallel within a shell 10 having a gas introducing port 8 and an exhaust port 9. Isolation walls 11a, 11a', 11b, 11b' are provided so that gas to be treated from the inlet 8 is not mixed with each other between going way (a, b, c) and return way (d, e, f). Heat required for reaction is supplied by a heater 13. As reactor and heat exchanger are combined, heat recovery rate is improved. As the surface area of catalyst is increased, the oxidation reactivity is improved.

Data supplied from the **esp@cenet** database - Worldwide